

Sanitary Units

Type Summary

Dimensions:

Width: 2,438 mm

Bright height: 2,500 mm

Length: 6,058 mm

Weight approx.:

Suitable for up to ... persons

Washbasin, warm and cold, with ... taps, with mirror

Washbasin, warm and cold, with mirror, and towel hook

Plastic shower cabin, with plastic curtain, soap holder, towel hook and mixer tap, 80 x 80 x 206 cm

Urinal basins with stop valve






Toilet-cabin with door, turn-lock Fastener, Flushdown toilet with flush down box, toilet paper holder and clothes peg

Electrical water heater, brand manufacture

Electrical quick heaters with Continuously adjustable temperature selector and thermostat 2000 W

Frost controllers, 500 W

Electrical wall fan, with pipe extension

	INS1 Wash- Shower-unit	INS2 Wash- Shower- WC-unit	INS3 Ladies- and Men- WC-unit	XNS4 Wash- Shower- WC-unit	XNS5 Ladies- and Men- WC-unit
					
	3,300 kg	3,800 kg	3,500 kg	2,900 kg	2,900 kg
	50	25	50	10	20
	6	2			
		1	2	1	2
	4	2		1	
		2	3	1	1
		2	3 + 1	1	2
	400 L	300 L	5 L / 5 L	80 L / 5 L	5 L / 5 L
	1	2	1	2	1
		1	1	1	2
		2	1		

Sanitary - Facilities

Excerpts from place of work regulations (ASV) and place of work guidelines (ASR)

**§ ASV 45
Day accommodation
on Construction sites**

- (4) From 15th October until 30th April
 1. Day accommodation heating - facility must enable a room temperature of + 21 °C ... and
 2. exits leading directly outside must be fitted with a wind screen.

**§ ASV of 47
washrooms for ten or
more employees on
construction sites**

- (1) If ten or more employees are employed longer than two weeks on a construction site by an employer, the employer must provide special washrooms. This is not valid when employees of the construction site regularly return to a factory with washrooms after finishing work.
 (3) In the washrooms, one washing – location must be provided for at least every five employees and one shower with hot and cold running water for at least every 20 employees. There must be enough free space by every wash location for the employees to wash themselves freely.

**ASR 35/1-4
Washrooms**

- 5.2 The number of wash locations is determined as follows:
 - a washing - location for five employees with moderate soiling activities
 - a washing - location for four employees in all other cases.
 5.3 washing – locations are permitted to be:
 - Wash channels with several washing - locations (washing - bays)
 - Washbasins with single washbasins or as washing benches
 - Washing - fountain
 - Showers
 5.4 A third of the washing locations determined by 5.2 consist of showers with heavy soiling activities must; with at least one shower available. If the employees are exposed to infectious, toxic, harmful materials etc, one shower must be available for every four employees.

**§ ASV 48
Toilet facilities on
construction sites**

- (1) At least one lockable toilet must be available on or nearby every construction site.
 (2) If fifteen or more employees are employed longer than two weeks on a construction site by an employer, he must provide toilet rooms with a sufficient number of toilets, conveniences and washing - locations. The toilet rooms must be ventilated, illuminated and heated from 15.10. to 30.4.

**ASR 37/1
Toilet rooms /
toilets made available**

The number of required toilets and conveniences can be established with the following table according to DIN 18 228 sheet 3:

Men

Number of employees, up to	5	10	25	50	75	100	130	160	190	220	250
Number of toilets	1	1	2	3	4	5	6	7	8	9	10
Number of conveniences		1	2	3	4	5	6	7	8	9	10

Women

Number of employees, up to	5	10	20	35	50	65	80	100	120	140	160
Number of toilets	1	1	2	3	4	5	6	7	8	9	10

2.2 A toilet room should not contain more than 10 toilet cabins and 10 conveniences.

Subject to modifications.